

ELECTRODE STRUCTURE FOR USE IN AN INTEGRATED CIRCUIT

Field of the Invention

5 The present invention relates generally to semiconductor chips and integrated circuits, and more particularly to an electrode structure for use in integrated circuits, such as electronic systems, memory systems and the like.

Background of the Invention

10 In fabricating integrated circuits, semiconductor chips and the like, chemical/mechanical planarization can be used as an intermediate operation to planarize a structure to provide a uniform, level surface for subsequent processing operations in the manufacturing of a semiconductor chip or integrated circuit. For example, electrodes or electrical contacts between different layers of conductive
15 materials in a semiconductor chip can be formed by depositing a first layer of conductive material, typically a metal, although a semiconductor material could be used as well, and then depositing a thin dielectric layer over the first conductive layer. The dielectric layer is then patterned to form at least one opening in the dielectric layer to expose a portion of the surface of the first conductive layer. The
20 opening can have a small aspect ratio of depth to width. For instance, the opening can be about half a micron wide but only about 500 angstroms deep thus presenting a aspect ratio of about 0.1. A second layer of a different conductive material is then deposited on the dielectric layer and in the opening on the first conductive layer to make electrical contact through the opening with the first conductive layer. The
25 second conductive layer is then removed form the dielectric layer or planarized to expose the dielectric layer and to form an isolated electrode or damascene contact structure in the opening before subsequent fabrication operations. In removing the second conductive layer by chemical/mechanical processing or planarization (CMP), the forces created by the CMP process can have a tendency to force the conductive
30 material of the second layer out of the opening thereby destroying the contact.

Accordingly, for the reason stated above, and for other reasons that will become apparent upon reading and understanding the present specification, there is a need for an electrode structure and method of fabrication that provides substantially improved adhesion between a first layer of conductive material and
5 second layer of a different conductive material, particularly during a CMP operation, and that does not adversely effect the conductivity between the two layers or create an electrical barrier. There is also a need for a method of fabricating an electrode structure that does not effect or damage other components that may already have been formed on the same wafer or substrate and that does not adversely effect the
10 manufacturing process by requiring a significant number of additional process operations.

Summary of the Invention

The above mentioned problems with electrode structures are addressed by
15 the present invention and will be understood by reading and studying the following specification. Electrode structures, memory cells and systems are provided by the present invention that exhibit good adhesion between different conductive layers during manufacturing operations such as CMP without the conductivity between the layers being adversely effected. Methods of fabricating are also provided by the
20 present invention that do not adversely effect other components that may have already been formed on a semiconductor die.

In accordance with the present invention, an electrode structure includes a first layer of conductive material and a dielectric layer formed on a surface of the first layer. An opening is formed in the dielectric layer to expose a portion of the
25 surface of the first layer. A binding layer is formed on the dielectric layer and on the exposed portion of the surface of the first layer and a second layer of conductive material is formed on the conductive binding layer.

In accordance with an embodiment of the present invention, a memory cell, includes a first layer of conductive material and a dielectric layer formed on a
30 surface of the first layer. An opening is formed in the dielectric layer to expose a

portion of the surface of the first layer. A binding layer is formed on the dielectric layer and on the exposed portion of the surface of the first layer and a second layer of conductive material is formed on the binding layer. A layer of doped chalcogenide material is formed on the second layer of conductive material and a
5 third layer of conductive material is formed on the layer of doped chalcogenide material.

In accordance with another embodiment of the present invention, a method of making an electrode, comprises: forming a first layer of conductive material; forming a dielectric layer on a surface of the first layer; forming an opening in the
10 dielectric layer to expose a portion of the surface of the first layer; forming a binding layer on the dielectric layer and on the exposed portion of the surface of the first layer; and forming a second layer of conductive material on the binding layer. The electrode structure can be annealed at a selected temperature for a predetermined time period to cause conductive material from the second layer to be diffused into
15 the binding layer to improve adhesion and conductivity between the first and second conductive layers.

In accordance with another embodiment of the present invention, a method of making a memory cell, comprises: forming a first layer of conductive material; forming a dielectric layer on a surface of the first layer; forming an opening in the
20 dielectric layer to expose a portion of the surface of the first layer; forming a binding layer on the dielectric layer and on the exposed portion of the surface of the first layer; forming a second layer of conductive material on the binding layer; forming a layer of doped chalcogenide material on the second layer of conductive material; and forming a third layer of conductive material on the layer of doped chalcogenide
25 material. The layer of chalcogenide material can be doped by annealing the memory cell to cause conductive material from the third layer to be chemisorbed into the chalcogenide layer.

These and other embodiments, aspects, advantages and features of the present invention will be set forth in part in the description which follows, and in
30 part will become apparent to those skilled in the art by reference to the following

description of the invention and referenced drawings or by practice of the invention. The aspects, advantages, and features of the invention are realized and attained by means of the instrumentalities, procedures, and combinations particularly pointed out in the appended claims.

5

Brief Description of the Drawings

In the drawings, like numerals describe substantially similar components throughout the several views. Like numerals having different letter suffixes or primed (X') represent different occurrences of substantially similar components.

10 Figures 1A-1C illustrate the operations in forming an electrode for use in an integrated circuit in accordance with the present invention.

Figures 2A-D illustrate the operations in forming a programmable memory cell in accordance with an embodiment of the present invention.

15 Figures 3A-3E illustrate the operations in forming a programmable memory cell in accordance with another embodiment of the present invention.

Figure 4 is a schematic diagram of a memory system incorporating a programmable memory cell in accordance with the present invention.

Figure 5 is a top view of a wafer or substrate containing semiconductor dies in accordance with an embodiment of the present invention.

20 Figure 6 is a block schematic diagram of a circuit module in accordance with an embodiment of the present invention.

Figure 7 is a block schematic diagram of a memory module in accordance with an embodiment of the present invention.

25 Figure 8 is a block schematic diagram of an electronic system in accordance with another embodiment the present invention.

Figure 9 is a block schematic diagram of a memory system in accordance with an embodiment of the present invention.

Figure 10 is a block schematic diagram of a computer system in accordance with an embodiment of the present invention.

30

Description of the Embodiments

In the following detailed description of the preferred embodiments, reference is made to the accompanying drawings which form a part hereof, and in which is shown by way of illustration specific embodiments in which the invention may be practiced. These embodiments are described in sufficient detail to enable those skilled in the art to practice the invention, and it is to be understood that other embodiments can be utilized and that process or mechanical changes may be made without departing from the scope of the present invention. The terms wafer and substrate used in the following description include any base semiconductor structure. Both are to be understood as including silicon-on-sapphire (SOS) technology, silicon-on-insulator (SOI) technology, thin film transistor (TFT) technology, doped and undoped semiconductors, epitaxial layers of a silicon supported by a base semiconductor, as well as other semiconductor support structures well known to one skilled in the art. Furthermore, when reference is made to a wafer or substrate in the following description, previous process operations may have been utilized to form regions/junctions in the base semiconductor structure. The following detailed description is, therefore, not to be taken in a limiting sense, and the scope of the present invention is defined only by the appended claims.

The transistors described herein include transistors from bipolar-junction technology (BJT), field effect technology (FET), or complimentary metal-oxide-semiconductor (CMOS) technology. A metal-oxide-semiconductor (MOS) transistor includes a gate, a first node (drain) and a second node (source). Since a MOS transistor is typically a symmetrical device, the true designation of "source" and "drain" is only possible once voltage is impressed on the terminals. The designations of source and drain herein should be interpreted, therefore, in the broadest sense. It should also be noted that a P-channel MOS transistor could alternatively be used for an N-channel MOS transistor and vice versa with the polarity of the associated gate voltages merely being reversed. For example, applying a negative gate voltage in the situation of a P-channel MOS transistor to

activate the transistor and reversing the polarity to apply a positive gate voltage to activate an N-channel transistor if an N-channel MOS transistor is substituted for a P-channel transistor.

Figures 1A-1C illustrate the operations in forming an electrode structure 100 in accordance with the present invention. In Figure 1A, a first layer 102 of conductive material is deposited or formed. The first layer 102 of conductive material can be tungsten, nickel or a semiconductor material. A dielectric layer 104 is formed on the first conductive layer 102. The dielectric layer 104 can be a nitride, such as silicon nitride or a similar dielectric material. The dielectric layer 104 is patterned by standard photolithographic techniques or the like to form at least one opening 106 through the dielectric layer 104 to expose a portion of a surface 108 of the first conductive layer 102. The opening 106 can have a width "W" or a diameter that is significantly larger than a depth "D" to provide a small aspect ratio; however, the invention is not limited to such aspect ratios. A layer 110 of oxide is formed on the dielectric layer 104 and on the surface 108 of the first conductive layer 102. The oxide layer 110 can be a silicon oxide deposited by the thermal reaction of a precursor, such as tetraethyl orthosilicate (TEOS) or the like. The oxide layer 110 can have a thickness between about 50 angstroms and about 200 angstroms. A second layer 112 of conductive material is formed on the oxide layer 110. The second layer 112 of conductive material can be silver, nickel or another metal or conductive material that can diffuse into the oxide layer 110 and bond to the oxide layer 110.

In Figure 1B, the electrode structure 100B is annealed in an inert ambient environment at a selected temperature for a predetermined time period. The inert ambient environment can be nitrogen, argon or some other gas that is non-reactive to the materials forming the electrode structure 100. For an oxide layer 110 of TEOS and a second conductive layer 112 of silver, annealing at about 350° Celsius for about ten minutes provides the proper amount of diffusion or chemisorption of silver molecules into the TEOS to make the oxide layer 110 at least semiconductive so as to not create an electrical barrier between the first and second conductive

layers 102 and 112. The oxide layer 110 is therefore converted into a conductive or at least semiconductive binding layer 110' by the annealing operation. The electrode structure 100B can be annealed at temperatures as low as about 130° Celsius or room temperature; however, the time period to achieve the proper level of chemisorption will be much longer thereby increasing the amount of time overall for the manufacturing process. According to the present invention, the annealing temperature and time period can be adjusted to control the rate and amount of diffusion or chemisorption of molecules of the conductive material or metal from the second layer 112 into the oxide layer 110. The annealing temperature and time period are also selected with consideration of other components and subsequent processing steps so as to not adversely effect or damage other components that have already been formed on a wafer or semiconductor die or that would result in additional processing operations that would increase the cost and time to manufacture a semiconductor chip.

In Figure 1C, the electrode structure can be planarized to form an isolated electrode structure or damascene layer 114 and to form a level or more uniform surface 116 for subsequent processing operations. The planarization of the electrode structure 100C can be accomplished by a chemical/mechanical planarization (CMP) process or the like. In accordance with the present invention, the binding layer 110' is selected to provide sufficient adhesion between the first and second conductive layers 102 and 112 to prevent the forces created by the CMP process from forcing or warping out the damascene layer 114.

In Figures 2A-2D, the process operations are shown to form a programmable memory or metallization cell structure 200 in accordance with an embodiment of the present invention that can be used in a memory system, such as a programmable cell random access memory (PCRAM) device or the like. In Figure 2A, a first conductive layer 202 is formed. The first conductive layer 202 can be a metal, such as tungsten, nickel or the like, or the first conductive layer 202 can be a semiconductor or polysilicon material. A layer 204 of dielectric material is formed on the first conductive layer 202. The dielectric layer 204 can be a nitride, for

example silicon nitride or a similar dielectric. The dielectric layer 204 is selectively patterned by standard photolithographic techniques or similar material removal techniques to form at least one opening 206 in the dielectric layer 204 and to expose a portion of a surface 208 of the first conductive layer 202. The opening 206 can have a depth dimension "D" that is much smaller than a width dimension "W" to define a small aspect ratio of depth to width. The invention, however, is not so limited. A layer 210 of oxide is formed on the dielectric layer 204 and on the exposed surface portion 208 of the first conductive layer 202. The oxide layer 210 can be a silicon dioxide. The oxide layer 210 can have a thickness between about 50 angstroms and about 100 angstroms. A second layer 212 of conductive material is formed on the oxide layer 210 and in the opening 206. The second conductive layer 212 can be a metal, such as silver, nickel, polysilicon or other conductive material that is diffusible into an oxide and exhibits good adhesion to an oxide. The second conductive layer can have a thickness between about 50 angstroms and about 500 angstroms depending upon other parameters or features of the memory cell structure 200.

In Figure 2B, the memory cell structure 200B is annealed at a selected temperature for a predetermined time period in an inert ambient environment, such as nitrogen, argon or some other gas that is non-reactive to the materials forming the cell structure 200. As an example, for an oxide layer 210 of TEOS and a second conductive layer 212 of silver, annealing at about 350° Celsius for about 10 minutes provides the appropriate level of diffusion or chemisorption of silver molecules into the TEOS oxide layer 210 to make the oxide layer 210 at least semiconductive so as to not create an electrical barrier between the first and second conductive layers 202 and 212. The oxide layer 210 becomes a conductive or semiconductive binding layer 210' as a result of the annealing operation and provides stronger adhesion between the first and second conductive layers 202 and 212 as a result of the annealing process for stability of the structure 200 during subsequent manufacturing operations such as CMP. As one of ordinary skill in the art will understand by reading and comprehending this disclosure, the annealing temperature and time can

be adjusted to control the rate and amount of chemisorption of silver or conductive material from the second conductive layer 212 into the oxide layer 210 and to also control the impact on previously formed structures or devices on the wafer or semiconductor chip. Because of the diffusion of conductive material during the annealing process, the resulting conductive binding layer 210' defines an electrical contact or interface between the first and second conductive layers 202 and 212.

In Figure 2C, a layer 214 of chalcogenide glass material is formed on the on the second conductive layer 212 and in the opening 206. The layer 214 of chalcogenide glass material can be germanium selenide ($\text{Ge}_x\text{Se}_{1-x}$, where X is the concentration of germanium and 1-X is the concentration of selenide). In one embodiment according to the teachings of the present invention, the concentration ratio of germanium to selenide can be between about 15/85 and about 40/60. A third layer 216 of conductive material is formed on the layer 214. The third conductive layer 216 can be a metal such as silver, nickel or another metal that is diffusible into a chalcogenide material. The layer 214 is doped by annealing the memory cell structure 200C to cause metal or conductive material from the third layer 216 to diffuse into the chalcogenide layer 214 to a selected concentration. The annealing process can be ultra violet annealing or a similar annealing process. The annealing process also improves adhesion between the third conductive layer 216 and the chalcogenide layer 214 resulting in a highly adhesive cell structure 200C that can withstand the forces or pressures applied by subsequent manufacturing operations such as CMP.

In Figure 2D, the cell structure 200D is planarized to form an isolated cell structure 200D or third layer contact or damascene layer 216' and to provide a level or more uniform surface 218 for subsequent processing operations. The cell structure 200D can be planarized by CMP or the like. A fourth layer 220 of conductive material can be formed on the planarized surface 218 and in electrical contact with the third layer contact 216'.

The conductive material or metallization of the second layer 212 formed on the sidewalls 222 of the opening 206 can be minimized by the deposition process

and is substantially diffused into the oxide layer 210 on the sidewalls 222 during the annealing process. In this manner, no isolation or dielectric is required between any residual metallization on the sidewalls 222 and the fourth layer of conductive material 220 that would necessitate additional process steps after the CMP operation
5 and before the fourth layer 220 is formed.

Figures 3A-3E illustrate the operations in forming a programmable memory cell 300 in accordance with another embodiment of the present invention that forms a reentrant profile to prevent conductive material from forming on the sidewalls of the opening in the dielectric layer. In Figure 3A, a first conductive layer 302 is
10 formed. The first conductive layer 302 can be a metal such as tungsten, nickel, or the like, or a semiconductor material or polysilicon. A first dielectric layer 304 having one etch rate is formed on the first conductive layer 302 and a second dielectric layer 306 having a second etch rate is formed on the first dielectric layer 304. In accordance with the present invention, the etch rate of the first dielectric
15 layer 304 is faster than the etch rate of the second dielectric layer 306. Accordingly, in Figure 2B, when the first and second dielectric layers 304 and 306 are selectively patterned to form an opening 308, the opening has a reentrant profile with sidewalls 310 that angle back as the opening 308 extends down to expose the first conductive layer 302. A layer 312 of oxide is formed on the second dielectric layer 306 and on
20 an exposed surface portion 314 of the first conductive layer 302 in the opening 308. The oxide layer 312 can be a silicon oxide. A second layer 316 of conductive material is formed on the oxide layer 312. The second conductive layer 316 can be silver, nickel or another conductive material or metal that is diffusible into an oxide. Because of the reentrant profile of the opening 308, the second conductive layer 316
25 and oxide layer 312 cannot form on the sidewalls 310 of the opening 308.

In Figure 3C, the cell structure 300C is annealed at a selected temperature for a predetermined time period to cause metallization or conductive material from the second conductive layer 316 to diffuse into the oxide layer 312 to form a conductive binding layer 312'. The conductive binding layer 312' provides electrical
30 contact and adhesion between the first and second conductive layers 302 and 316

during subsequent processing operations such as CMP. As previously discussed, the annealing temperature and time can be adjusted to control the amount of chemisorption of metal molecules into the oxide layer 312 and to control the impact on other components or devices already formed on the wafer or semiconductor chip.

5 In Figure 3D, a layer 318 of chalcogenide glass material is formed on the on the second conductive layer 316 and in the opening 308. The layer 318 of chalcogenide glass material can be germanium selenide ($\text{Ge}_x\text{Se}_{1-x}$, where X is the concentration of germanium and 1-X is the concentration of selenide). As previously discussed, according to the teachings of the present invention, the concentration ratio of germanium to selenide can be between about 15/85 and about 10 40/60. A third layer 320 of conductive material is formed on the layer 318. The third conductive layer 318 can be a metal such as silver, nickel or another metal that is diffusible into a chalcogenide material. The layer 318 is doped by annealing the memory cell structure 300D to cause metal or conductive material from the third 15 layer 320 to diffuse into the chalcogenide layer 318 to bond the two layers together and provide better adhesion.

In Figure 3E, the cell structure 300E is planarized to form an isolated cell structure 300E including an isolated third layer contact or electrode 320'. The planarization also provides a level, more uniform surface 322 for subsequent 20 processing operations. The cell structure 300E can be planarized by CMP or the like. A fourth layer 324 of conductive material can be formed on the planarized surface 322 and in electrical contact with the third layer electrode or contact 320'.

In operation, the programmable memory cell 200 or 300 or programmable metallization cell can be programmed by applying a potential or voltage across the 25 first layer or electrode 302 and the third layer electrode 320' that has a sufficient voltage level to cause a dendrite 326 or conductive filament to be formed between the electrode 320' and the second conductive layer 316 which is electrically connected to the first layer electrode 302 by the conductive binding layer 312'. Because the chalcogenide layer 322 is doped with a metal or conductive material 30 such as silver, the voltage causes the dendrite 326 (226 in Figure 2D) to be formed

to short circuit the two electrodes 320' and 302. The resistance across a cell 300 that has been biased by applying sufficient voltage to form the dendrite 326 is about 10,000 ohms. The resistance of a cell 300 that has not been biased and is in an open condition is about 10 megohms. Accordingly, a programmed cell 300 to which a voltage has been applied to form the dendrite 326 can represent a logic 1 and an unprogrammed or open cell 300 can represent a logic 0. To erase a programmed cell 300, a reverse polarity voltage can be applied to the electrodes 320' and 302 of the cell 300 to cause sufficient current to flow through the cell 300 to return the cell 300 to a high resistance state by destruction of the dendrite 326 or conductive element.

Figure 4 is a schematic diagram of a memory device or system 400 in accordance with the present invention. The memory system 400 includes a plurality of memory elements 402 that can be arranged in rows and columns. Each memory element 402 can include a transistor 404. Each transistor 404 includes a gate electrode 406 coupled to an address line 408 for controlling the operation of the memory element 402, and each transistor 404 includes a first source/drain electrode 410 coupled to a data line 412 and a second source/drain electrode 414 coupled to a programmable memory cell 416 according to the teachings of the present invention, e.g. similar to the memory cells 200D (Figure 2D) and 300E (Figure 3E).

With reference to Figure 5, a semiconductor die 510 can be produced from a silicon wafer 500 that can contain a memory system similar to system 400 or an electronic system including the novel electrode structure 100C (Figure 1E) or memory cells 200D (Figure 2D) or 300E (Figure 3E) in accordance with the present invention. A die 510 is an individual pattern, typically rectangular, on a substrate that contains circuitry to perform a specific function. A semiconductor wafer 500 will typically contain a repeated pattern of such dies 510 containing the same functionality. Die 510 can further contain additional circuitry to extend to such complex devices as a monolithic processor with multiple functionality. Die 510 is typically packaged in a protective casing (not shown) with leads extending

therefrom (not shown) providing access to the circuitry of the die 510 for unilateral or bilateral communication and control.

As shown in Figure 6, two or more dies 510, including at least one electronic system or memory system 400 that incorporates the novel electrode structure 100C or memory cells 200D or 300E in accordance with the present invention, can be combined, with or without a protective casing, into a circuit module 600 to enhance or extend the functionality of an individual die 510. Circuit module 600 can be a combination of dies 510 representing a variety of functions, or a combination of dies 510 containing the same functionality. Some examples of a circuit module 600 include memory modules, device drivers, power modules, communication modems, processor modules and application-specific modules and can include multi-layer, multi-chip modules. Circuit module 600 can be a sub-component of a variety of electronic systems, such as a clock, a television, a cell phone, a personal computer, an automobile, an industrial control system, an aircraft and others. Circuit module 600 will have a variety of leads 610 extending therefrom providing unilateral or bilateral communication and control.

Figure 7 shows one embodiment of a circuit module as a memory module 700 containing circuitry for the memory system 400 including the electrode structure 100C or memory cell structures 200D or 300E of the present invention. Memory module 700 generally depicts a Single In-line Memory Module (SIMM) or Dual In-line Memory Module (DIMM). A SIMM or DIMM can generally be a printed circuit board (PCB) or other support containing a series of memory devices. While a SIMM will have a single in-line set of contacts or leads, a DIMM will have a set of leads on each side of the support with each set representing separate I/O signals. Memory module 700 contains multiple memory devices 710 contained on support 715, the number depending upon the desired bus width and the desire for parity. Memory module 700 can contain memory devices 710 on both sides of support 715. Memory module 700 accepts a command signal from an external controller (not shown) on a command link 720 and provides for data input and data output on data links 730. The command link 720 and data links 730 are connected

to leads 740 extending from the support 715. Leads 740 are shown for conceptual purposes and are not limited to the positions shown in Figure 7.

Figure 8 shows an electronic system 800 containing one or more circuit modules 600 as described above containing the novel memory system 400 and electrode structure 100C or memory cells 200D or 300E of the present invention. Electronic system 800 generally contains a user interface 810. User interface 810 provides a user of the electronic system 800 with some form of control or observation of the results of the electronic system 800. Some examples of user interface 810 include the keyboard, pointing device, monitor and printer of a personal computer; the tuning dial, display and speakers of a radio; the ignition switch and gas pedal of an automobile; and the card reader, keypad, display and currency dispenser of an automated teller machine. User interface 810 can further describe access ports provided to electronic system 800. Access ports are used to connect an electronic system to the more tangible user interface components previously exemplified. One or more of the circuit modules 600 can be a processor providing some form of manipulation, control or direction of inputs from or outputs to user interface 810, or of other information either preprogrammed into, or otherwise provided to, electronic system 800. As will be apparent from the lists of examples previously given, electronic system 800 will often contain certain mechanical components (not shown) in addition to the circuit modules 600 and user interface 810. It will be appreciated that the one or more circuit modules 600 in electronic system 800 can be replaced by a single integrated circuit. Furthermore, electronic system 800 can be a sub-component of a larger electronic system.

Figure 9 shows one embodiment of an electronic system as memory system 900. Memory system 900 contains one or more memory modules 700 as described above including the memory system 400 and electrode structure 100C or memory cells 200D and 300E in accordance with the present invention and a memory controller 910. Memory controller 910 provides and controls a bidirectional interface between memory system 900 and an external system bus 920. Memory system 900 accepts a command signal from the external bus 920 and relays it to the

one or more memory modules 700 on a command link 930. Memory system 900 provides for data input and data output between the one or more memory modules 700 and external system bus 920 on data links 940.

Figure 10 shows a further embodiment of an electronic system as a computer system 1000. Computer system 1000 contains a processor 1010 and a memory system 900 housed in a computer unit 1005. Computer system 1000 is but one example of an electronic system containing another electronic system, i.e. memory system 900, as a sub-component, including the memory system 400 and electrode structure 100C or memory cells 200D and 300E in accordance with the present invention. Computer system 1000 optionally contains user interface components. Depicted in Figure 10 are a keyboard 1020, a pointing device 1030, a monitor 1040, a printer 1050 and a bulk storage device 1060. It will be appreciated that other components are often associated with computer system 1000 such as modems, device driver cards, additional storage devices, etc. It will further be appreciated that the processor 1010 and memory system 900 of computer system 1000 can be incorporated on a single integrated circuit. Such single package processing units reduce the communication time between the processor 1010 and the memory system 900.

Conclusion

The present invention thus provides an electrode structure and memory cell structure and method of fabrication that provides substantially improved adhesion between two layers of conductive material during subsequent processing operations, such as a CMP operation. The electrode structure and memory cell structure of the present invention also can provide a conductive interface between the two conductive layers that is not an electrical barrier and can provide a doped glass layer that can be programmed to store data. The present invention also provides a method of fabricating an electrode structure or memory cell structure that does not adversely effect subsequent processing operations or require additional processing operations

and the process can be controlled to avoid damage to other components that may already have been formed on the same wafer or substrate.

Although specific embodiments have been illustrated and described herein, it will be appreciated by those of ordinary skill in the art that any arrangement which
5 is calculated to achieve the same purpose may be substituted for the specific embodiments shown. This application is intended to cover any adaptations or variations of the present invention. Therefore, it is intended that this invention be limited only by the claims and the equivalents thereof.

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221